

\* SIGNAL HEAD | ARROWS ARE COVERED.

# PROJECT CONTACTS

THE CONTACT PERSONS FOR DISTRICT #3 ARE AS FOLLOWS:

MR. CHARLIE WATKINS DISTRICT ENGINEER PHONE: (301) 513-7311

MR. MAJID SHAKIB ASSISTANT DISTRICT ENGINEER - TRAFFIC PHONE: (301) 513-7358

MR. JOE GECKLE
UTILITY ENGINEER
PHONE: (301) 513-7350

MR. RICHARD L. DAFF, SR. CHIEF, TRAFFIC OPERATIONS DIVISION PHONE: (410) 787-7630

THE POWER COMPANY REPRESENTATIVE IS:
BALTIMORE GAS AND ELECTRIC COMPANY
MR. JOSEPH G. BUNCH
SUPERVISOR
INDUSTRIAL/COMMERCIAL SERVICES
NEW BUSINESS CONSTRUCTION
PHONE: (410) 859-9030

# PROJECT DESCRIPTION

THIS PROJECT INVOLVES THE MODIFICATION OF THE TRAFFIC SIGNAL AT MD 197 AND B/W PARKWAY NORTHBOUND RAMP (RAMP C-I) IN PRINCE GEORGE'S COUNTY. MD 197 IS ASSUMED TO RUN IN A NORTH SOUTH DIRECTION.

INTERSECTION OPERATION

I. NORMAL OPERATION

DURING TRAFFIC CONTROL STAGE 4 THE INTERSECTION WILL OPERATE IN A NEMA (4) FOUR-PHASE FULL-TRAFFIC-ACTUATED MODE WITH SOUTHBOUND AND NORTHBOUND MARYLAND 197 APPROACHES OPERATING CONCURRENTLY. THE RAMP FROM B/W PARKWAY AND SNOWDON ROAD APPROACHES WILL OPERATE AS SPLIT PHASES.

#### MAINTENANCE OF TRAFFIC

THE TRAFFIC CONTROL NUMBERS SHALL BE REFERENCED FOR THE PROJECT

STANDARD NO. MD-IO5.00
STANDARD NO. MD-IO5.01
STANDARD NO. MD-IO5.02
STANDARD NO. MD-IO5.IOI (FLAGGING OPERATION)
STANDARD NO. MD-IO5.IO3 (INTERSECTION FLAGGING OPERATION)
STANDARD NO. MD-IO5.IO5 (SHOULDER WORK)
STANDARD NO. MD-IO5.IO7 (LANE SHIFT)
STANDARD NO. MD-IO5.IO9 (LANE SHIFT)

NOTE: STANDARDS TO BE MODIFIED BY REPLACING

W21-5 SIGN WITH A W29-1 SIGN (ROAD WORK AHEAD).

MIL DISCONNECT EXISTING LOOP DETECTOR AND WHE NOW LOOP DETECTOR AND WHE NOW LOOP DETECTOR AND WHE NOW LOOP DETECTOR TO EXISTING CABLE

- A 2 CONDUCTOR ELECTRICAL CABLE (ALUMINUM SHIELDED.) SPLICE
- B MICRO-LOOP PROBE SET
- LW LOOP WIRE (NO.14 A.W.G.)
- ES EXISTING SERVICE
- +  $-\frac{3}{4}$ " × 10' GROUND ROD
- ML MICRO-LOOP PROBE SET

# EQUIPMENT LIST "B"

B. EQUIPMENT TO BE FURNISHED AND/OR INSTALLED BY THE CONTRACTOR

SPEC. SECTION	CATEGORY CODE No.	QUANTITY	DESCRIPTION
104	120500	L.S.	MAINTENANCE OF TRAFFIC
805	805160	5 L.F.	FURNISH AND INSTALL I IN. LIQUID TIGHT FLEXIBLE NON-METALLIC CONDUIT FOR DETECTOR SLEEVE
810	862101	560 L.F.	FURNISH AND INSTALL LOOP WIRE ENCASED IN FLEXIBLE TUBING (NO.14 AWG)
815	862102	510 L.F.	FURNISH AND INSTALL SAW CUT FOR SIGNAL (LOOP DETECTOR)
810	810011	I EACH	FURNISH AND INSTALL LOOP DETECTOR SPLICE TO EXISTING 2-CONDUCTOR (ALUMIUM SHIELDED) CABLE
	114245	38 LF	FURNISH AND INSTALL 24 IN. WHITE REMOVABLE PREFORMED PAVEMENT MARKING TAPE (STOP LINE)
	100000	25 LF	FURNISH AND INSTALL 5" WHITE REMOVABLE PREFORMED PAVEMENT MARKING TAPE
810	800000	I EACH	MICRO LOOP PROBE SET WITH 1,000 FT. LEAD-IN.
813	800000	9 SF	INSTALL OVERHEAD SIGN.
805	805011	15 LF	FURNISH AND INSTALL I'GALVANIZED ELECTRICAL CONDUIT FOR DETECTER SLEEVE.

# CONSTRUCTION DETAILS

STAGE 4

- A. INSTALL 1" LIQUID-TIGHT FLEXIBLE NON-METALLIC ELECTRICAL CONDUIT (DETECTOR WIRE SLEEVE).
- B. NOT USED.
- C. INSTALL 6' X 30' LOOP DETECTOR, ENCASED IN 1/4 IN. FLEXIBLE TUBING (3,6,3 TURNS). QUADRUPOLE TYPE.
- D. INSTALL 24 IN. WHITE REMOVABLE PREFORMED PAVEMENT MARKING TAPE (STOPLINE)
- E.NOT USED.
- F.SPLICE LOOP DETECTOR TO EXISTING 2-CONDUCTOR (ALUMINUM SHIELDED) CABLE.
- G.NOT USED.
- H. INSTALL 1" GALVANIZED ELECTRICAL CONDUIT FOR DETECTOR SLEEVE.
- I. INSTALL MICRO-LOOP PROBE SET WITH 1,000 FT. LEAD-IN.
- J.FURNISH AND INSTALL 5" WHITE REMOVABLE PREFORMED PAVEMENT MARKING TAPE.

ADDENDUM

STAGE 4 TEMPORARY TRAFFIC SIGNALS

SS-2I

